



GH Solar

Polycrystalline
PV Module

GH(260-290)P-60 Series

- ▶ High PID resist performance
- ▶ Excellent low light performance with advanced surface texturing and back surface field.
- ▶ Multi-busbar design decreases the risk of the cell micro-cracks and fingers broken.
- ▶ Lower series resistance/improved light harvesting enable high conversion efficiency and more power output.

260	270	275	280	285	290	System voltage 1000V/1500V standard	EN
-----	-----	-----	-----	-----	-----	-------------------------------------	----

ELECTRICAL SPECIFICATIONS						
STC rated output (P _{mpp})*	260 Wp	270 Wp	275 Wp	280 Wp	285 Wp	290 Wp
PV Module size	1640*992*35 MM					
Standard sorted output						
Warranted power output STC (P _{nominal})	260 Wp	270 Wp	275 Wp	280 Wp	285 Wp	290 Wp
Rated voltage (V _{mpp}) at STC	30.88 V	31.08 V	31.12 V	31.16 V	31.50 V	31.71 V
Rated current (I _{mpp}) at STC	8.43 A	8.70 A	8.85 A	8.99 A	9.05 A	9.15 A
Open circuit voltage (V _{oc}) at STC	37.72 V	38.00 V	38.45 V	38.85 V	38.70 V	39.05 V
Short circuit current (I _{sc}) at STC	8.95A	9.45 A	9.52 A	9.67 A	9.72 A	9.87 A
Module efficiency	16.0%	16.6%	16.9%	17.2%	17.5%	17.9%
Rated output (P _{mpp}) at NOCT	195.0 Wp	202.5 Wp	206.3 Wp	210.1 Wp	216.3 Wp	220.6 Wp
Rated voltage (V _{mpp}) at NOCT	27.94 V	28.12 V	28.15 V	28.17 V	28.75 V	28.17 V
Rated current (I _{mpp}) at NOCT	6.98 A	7.20 A	7.33 A	7.46 A	7.53 A	7.76 A
Open circuit voltage (V _{oc}) at NOCT	34.46 V	34.71 V	35.13 V	35.16 V	35.53 V	35.76 V
Short circuit current (I _{sc}) at NOCT	7.54 A	7.96 A	8.02 A	8.09 A	8.12 A	8.19 A

Temperature coefficient (P _{mpp})	- 0.407%/K	Maximum system voltage (IEC)	1000V _{DC} / 1500V _{DC}
Temperature coefficient (I _{sc})	+0.049%/K	Number of diodes	3
Temperature coefficient (I _{mpp})	- 0.000%/K	Maximum series fuse rating	15 A
Temperature coefficient (V _{mpp})	- 0.408%/K	Operating Temperature	-40°C to +85°C
Temperature coefficient (V _{oc})	- 0.310%/K		
Normal operating cell temperature (NOCT)	43±2°C		

* Measurement tolerance +/- 3%



GH Solar


12BB

RELATED PARAMETERS	
Cell type	Polycrystalline
Number of cells / cell arrangement	60 / 6 x10
Cells dimension	6"
Packing unit	30 modules
Weight of packing unit (for container)	557 kg / 1228 lbs


MECHANICAL SPECIFICATIONS	
Outer dimensions (L x W x H)	1640 x 992 x 35 mm 64.57 x 39.06 x 1.38 in
Frame technology	Aluminum, silver anodized
Module composition	Glass / EVA / Backsheet (white)
Weight (module only)	18 kg / 39.68 lbs
Front glass thickness	3.2 mm / 0.13 in
Junction box IP rating	IP 65/67
^① Cable length(IEC)	600/900 mm / 23.62/35.43 in
Cable diameter (IEC)	12 AWG /4 mm ²
^② Maximum load capacity	5400 Pa
Fire performance (IEC)	Class C
Connector type (IEC)	MC4 compatible

Refer to GH solar crystalline installation manual.

QUALIFICATION AND LINEAR WARRANTIES	
Product standard	IEC61215, 61730
Extended product warranty	12 years
Output decline 3%/year performance P _{mpp} (STC)	1 st year
Output decline 0.7%/year performance P _{mpp} (STC)	2 nd - 25 th years



I-V Curves of PV module MS260P-60 at various solar irradiance



MODULE DIMENSION DETAILS			
Front view	Side view	Rear view	Frame cross section

GH Solar Reserves the right of final interpretation.
Specifica tions and designs included in this datasheet are subject to change without notice.

GH SOLAR
Address: West xintiandi,Xiacheng Zone,hangzhou Zhejiang P.R.C
Website: www.ghsolarpanels.com